



Heat-curable surface-coating agents, and their use

Patent number: DE3311513
Publication date: 1984-10-04
Inventor: AHLERS KLAAS DR (DE); LOCH WERNER DR (DE);
OSTERLOH ROLF DR (DE); SCHUPP EBERHARD DR
(DE)
Applicant: BASF FARBEN & FASERN (DE)
Classification:
- International: C09D3/72; C09D3/64; C09D3/58; C09D3/80; C09D5/40;
B05D7/26; C25D13/06
- european: C08G18/58, C08G18/64C, C08G18/64F5, C08G18/69K,
C08G18/81K3B, C09D5/44K4, C08G18/58F
Application number: DE19833311513 19830330
Priority number(s): DE19833311513 19830330

Also published as:

 EP0123880 (A1)
 US4544687 (A1)

Abstract not available for DE3311513
Abstract of correspondent: **US4544687**

Heat-curable surface-coating agents which, for example in their protonated form, can be used in cathodic electrocoating contain, as a binder, a mixture of (A) a polyadduct, polycondensate or other polymer which has an average molecular weight \bar{M}_n of from 500 to 10,000 and, per molecule, on average two or more OH and/or NH groups and (B) a reaction product of a polyisocyanate and an olefinically unsaturated amine which carries a secondary amino group and a methacrylamide or methacrylate group.

Data supplied from the esp@cenet database - Worldwide